

DC300G-HF

DoP number:

0126DCD

1. Unique identification code of the product-type:

ASSA ABLOY DC300G-HF

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4) of the CPR:

ASSA ABLOY DC300G-HF electromagnetic hold open free swing surface mounted door closer

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

ASSA ABLOY, School Street, Willenhall, West Midlands WV13 3PW United Kingdom

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.

Standard: EN 1155: 1997:+ A1: 2002

Notified Certification Body No 1121

Certificate of Constancy of Performance: 1121-CPR-AE5015

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristic Ability to release	Performance	Harmonised technical Specification
5.2.1.Release from any angle	Pass	EN 1155:1997 + A1:2002
5.1.3. Not possible to inhibit the release	Pass	
5.1.4. Supply voltage	Pass	
5.1.5. External electrical connection	Pass	

5.1.6. Inlet for external wiring	Pass	
5.2.1. General		
5.2.2. Electrical release	Pass - Release within 3 s	
5.2.3. Door closing device EN 1154 requirements	EN 1154 (See DoP for ASSA ABLOY DC300 door closer)	
5.2.4. Durability	25K cycles –electrical switched 25K cycles -electrical	
5.2.5. Angle of hold open	Greater than 65°	
5.2.6. Manual release	Excess of 120 Nm	
5.2.7. Continuous hold open	Pass movement not more than 2° over 48 hours	
5.2.8. Overload performance	Pass	
5.2.9. Delayed release	N/A	
5.2.10 Electrical performance	Pass 5.2.7. and 5.2.9. verified at +/- 15% rated voltage	
5.1.11 Temperature rise	Pass At 15% rated voltage, operating coils/windings not more than 50°C; terminals and exposed surfaces not more than 25°	
5.1.12. Damage	Pass	
5.1.13. Fire/smoke doors	Grade 1	
Essential characteristic Durability of Self closing	Performance	Harmonised technical Specification
5.2.14.1. Corrosion	Grade 3: 96 hours	EN 1155:1997 + A1:2002
5.2.14.2. Corrosion	Pass	
Dangerous Substances Annex ZA3	Pass The materials in the product(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacture identified in point 4.

Signed for and on behalf of the manufacturer by:



Eryl Jones
Managing Director – ASSA ABLOY Door Hardware Group

ASSA ABLOY Opening Solutions UK & Ireland
Door Hardware Group
School Street
Willenhall
West Midlands
WV13 3PW

+44 (0)845 070 6713
customerservices@assaabloy.co.uk
www.assaabloyopeningsolutions.co.uk